

## **POTENTIAL OF USING ROSA CENTIFOLIA TO REMOVE IRON AND MANGANESE IN GROUNDWATER TREATMENT**

AeslinaBinti Abdul Kadir<sup>1</sup>, Norzila Binti Othman<sup>2</sup>, NurulAzimahBinti M.Azmi<sup>3</sup>

<sup>1,2,3</sup> Faculty of Civil and Environmental Engineering, Universiti Tun Hussein Onn Malaysia, Johor, Malaysia

\*Corresponding E-mail : [aeslina@uthm.edu.my](mailto:aeslina@uthm.edu.my)<sup>1</sup>  
[norzila@uthm.edu.my](mailto:norzila@uthm.edu.my)<sup>2</sup>  
[nurulazimah86@yahoo.com](mailto:nurulazimah86@yahoo.com)<sup>3</sup>

---

### **ABSTRACT**

Groundwater is source for water supply because of its good natural quality. However, groundwater may be exposed toward to contamination by various anthropogenic activities such as agricultural, domestic and industrial. Groundwater quality problem are typically associated with high hardness, high salinity and elevated concentration of iron, manganese, ammonium, fluoride and occasionally nitrate and arsenic. Therefore, groundwater should be treated to acceptable level before consumption. This study is carried out with the objectives to optimize the feasibility condition of contact time, biosorbent dosage and pH range in removing heavy metal by using Rosa Centifolia (*R. Centifolia*) and also to determine the water quality of groundwater sources. A dried Rosa Centifolia pretreated before being used as biosorbent. Experiment was done by varying contact time, biosorbent dosage and pH range to get the optimum value. The removal characteristic of Iron and Manganese by Rosa Centifolia was analyzed using Atomic Absorption Spectrophotometer (AAS). The optimum condition is achieved at 240 minutes, 0.05g/ml and pH 5 respectively. The optimum percentage removal of Iron and Manganese was found to be more than 70%. The finding indicated that Rosa Centifolia is a promising biosorbent in treating groundwater from RECESS UTHM wel.

**Keywords:** *Groundwater, Rosa Centifolia, Fe, Mn, Biosorption*

---

### **1.0 INTRODUCTION**

Most groundwater contains some metal such as iron and manganese which naturally leaches from rocks and soils [1,2,3]. These metals that are found naturally, in soils, rocks, plants and most water supplies are essential for human health [4,5]. Excess amounts of metal in drinking water can cause coloured water, rusty-brown stains or black specs on fixtures and laundry [6,7]. Excess amounts of metal may also affect the taste of beverages and can build up deposits in pipes, heaters or pressure tanks [8]. The accumulation of metal contamination in water has become a concern due to the growing health risk it poses to the public [9,10]. Exposure to heavy metal contamination has been found to cause kidney damage, liver damage, and anemia in low doses [11,12,13].

Due to the severity of heavy metal contamination and potential adverse health impact on the public, efforts must be taken to purify water containing toxic metal ions. However, the conventional methods for removing heavy metals from groundwater such as precipitation and sludge separation, chemical oxidation or reduction, ion exchange, reverse osmosis, membrane separation, electrochemical treatment and evaporation are often ineffective and costly when applied to dilute and very dilute effluents [14,15]. Due to this problem, in this study, the biosorption method was used to remove the pollutants. Biosorption is one of the alternative method to remove heavy metal [19,20]. This method was chosen due to its economical and will reduce the production of sludge at the end of treatment process. Recently, researchers have proven

to this alternative method by using many type of biomass waste that provides low cost maintenance but high removal efficiency of heavy metals [21,22]. Most studies prefer on choosing waste biomass that readily discard as waste in compare to costly biomass. *R. Centifolia* is one of the potential biomass that normally being discarded after extraction of essential oil that can be used as biosorbent to remove Fe and Mn in groundwater.

Commercially, *R. Centifolia* is used for its aesthetic value in perfumes manufacturing, decoration and healthy purpose. Normally, the number of rose consumptions is approximately 500 to 3000 petals roses in a year [23]. The *R. Centifolia* biomasses that were left after being used is a waste material with no commercial value or other usage. Hence, to reduce the waste of biomass, the *R. Centifolia* biomass was used as a biosorbent to solve this groundwater problem. The chemical composition of *R. Centifolia* waste biomass is described later on in this manuscript. In continuation of our investigation, the objective of this study was to determine the water quality of groundwater sources from RECESS, UTHM well. The effects of contact time, biosorbent dosage and pH range on Mn and Fe biosorption are described here in detail.

## **2.0 MATERIALS AND METHOD**

This study consists of comprehensive batch experimental work. Figure 2.1 shows the *R. Centifolia* that was used in this experiment. Groundwater samples were collected at RECESS UTHM in Parit Raja for the study. The method that was used to collect the groundwater sample is the grab method. In the experimental work, five stages of experiments were conducted.



**Figure 2.1:** *Rosa Centifolia*

Figure 2.2 shows the step of experimental work. Firstly, the groundwater quality was tested to determine the culprit heavy metals [24]. At the second stage, the treatment to treat the groundwater pollution was chosen. In this study, biosorption treatment using *R. Centifolia* in Figure 2.2 was chosen as the biosorbent to treat the groundwater pollution. Third stage is the preparation of *R. Centifolia* as the biosorbent. The used *R. Centifolia* was collected and was sun dried in 7 days. Then it was thoroughly washed with running water and three times with distilled water to remove dirt. The washed *R. Centifolia* was oven dried at 60oC for 72 hours until constant weight. Then, it was cut into small pieces with homogenous known particle size of less than 0.255 mm [25] and turned into powder using mixer. In the fourth stage, optimum condition for the biosorbent to remove the heavy metals was determined by making the biosorbent dosage, pH and contact time as the variables in the batch reactor conducted in the laboratory. Batch study was carried out in this stage. Last stage (5th stage), the optimum condition determined in batch reactor was applied repeatedly to confirm and determine the effectiveness of the removal. The rose waste biomass samples were analyzed using X-Ray Fluorescence (XRF) for trace metals. Kinetic experiments (30–330 min) were performed to evaluate the effect of contact time [46]. The

biomass (at 0.05 g/mL) was added into the conical flasks containing the 100mL of groundwater (100 mg/L) at pH 6. The flasks were agitated at 100rpm. In the dose (0.05–0.45 g/mL), size (less than 0.25mm), 100mL solution was taken in 250mL conical flask and were agitated at 100rpm for the initial contact time was maintained at the optimum value of 240min for Mn and Fe. In order to investigate the effect of pH in groundwater at various initial pH, it were prepared using 0.1MHCl or 0.1MNaOH. The optimum biomass for Mn and Fe (at 0.05 g/mL) was added into the conical flasks containing the 100mL of groundwater (100 mg/L). The flasks were agitated at 100rpm for 240 min. The metal concentrations were measured using atomic absorption spectrophotometer (AAS) (Perkin Elmer Analyst 300). The initial and final concentrations were determined using AAS. The amount of Fe and Mn taken up by rose waste biomass in each flask was calculated using following mass balance Equation 2.1 [26]:

$$\text{Percentage sorption} = \frac{C_i - C_e}{C_i} \times 100 \quad (\text{Equation 2.1})$$

Where:

$C_i$  = initial and equilibrium metal concentrations (mg/l)

$C_e$  = after treatment metal concentration (mg/l).




Figure 2.2: Experimental Work

### 3.0 RESULTS AND DISCUSSION


The chemical composition of R. Centifolia waste biomass is shown in Table 3.1. The obtained results clearly indicated that the rose waste biomass is cellulosic in nature and have replaceable hydrogen, alkali and alkaline metals. Thus, it can be regarded as potential Mn and Fe adsorbent. The effect of different experimental parameters on Mn and Fe biosorption is described in detail below.

**Table 3.1:** The elemental and proximate composition of Rosa centifolia waste biomass

Metal	Concentration (%)
CO <sub>2</sub>	0.10
K <sub>2</sub> O	62.90
CaO	9.72
P <sub>2</sub> O <sub>5</sub>	8.15
SO <sub>3</sub>	6.52
S <sub>i</sub> O <sub>2</sub>	4.38
MgO	3.30
Fe <sub>2</sub> O <sub>3</sub>	1.76
Cl	1.01
Al <sub>2</sub> O <sub>3</sub>	0.80
ZrO <sub>2</sub>	0.44
MnO	0.42
ZnO	0.28
Cr <sub>2</sub> O <sub>3</sub>	0.20
Rb <sub>2</sub> O	0.13

### 3.1 FOURIER TRANSFORMS INFRARED (FTIR) STUDIES

FTIR analysis is an important analytical tool for determination of functional groups responsible for heavy metal removal by R. Centifolia. Figure 3.1 show the peak frequency of functional group that contain in R. Centifolia.



**Figure 3.1:** FTIR spectra of R. Centifolia waste biomass.

In order to determine the functional groups responsible for metal uptake, the FTIR was employed as an analytical [27]. Figure 3.1 shows the raw spectrum of waste biomass sample. The spectra indicate the presence of different functional groups which are responsible for metal sorption process for example carboxylic acids display a broad intense -OH stretching absorption from 3300 to 2500  $\text{cm}^{-1}$ , amines (3393 $\text{cm}^{-1}$ ), esters (1065 $\text{cm}^{-1}$ ), and alkenyl (1628 $\text{cm}^{-1}$ ). The peak observed at 2920.28 $\text{cm}^{-1}$  are due to vibrations of OH and CO groups belonging to carboxylic acids. Nasir (2007) had pointed out that peak at position 2920.28 $\text{cm}^{-1}$  shifts towards higher wave number, which indicates involvement of this group in removal metals. Ester groups in the biomass produce carboxylate, which can bind cations. Another study by Padmavathy (2003) further proved that the peak at 1065 $\text{cm}^{-1}$  also shift towards higher wave number, which indicates involvement of this group in removal metals. It is shown that, chemical functional group in the biomass tends to interact with the metals ion, and it caused stretching, contraction and bending of its chemical bonds. It is expected that functional groups in *R. Centifolia* have high ability to absorb Fe and Mn.

### 3.2 EFFECT OF CONTACT TIME

The optimum contact time was determined based on the percentage removal efficiencies. The condition which had the highest removal efficiencies of Fe and Mn had been chosen as the optimum condition. Figures 3.2 shows the percentage removal of Fe and Mn at different contact times.





Figure 3.2: Effect of contact time to the removal efficiencies of Fe and Mn

From Figure 3.2 it was observed that the percentage removal of Fe and Mn ions by *R. Centifolia* increased with time and at 240min reached a constant value where no more removal increment were observed. At 240min the percentage removal of Fe is about 86.68% where for Mn the percentage removal is reached at 95.73%. At this point, the amount of metals being absorbed onto the biosorbent was in a state of dynamic equilibrium with the amount of absorb from the biosorbent [30]. The state of time required to attain this state of equilibrium was termed as the equilibrium time and the amount of metals absorbed at this equilibrium time reflected the maximum metals biosorption capacity of the biomass under the particular condition.

### 3.3 EFFECT OF BIOSORBENT DOSAGE

The optimum biosorbent dosage was also determined based on the percentage of the removal efficiencies. The condition which had the highest removal efficiencies of Fe and Mn had

been chosen as the optimum condition. Figures 3.3 show the percentage removal of Fe and Mn at different biosorbent dosage.



**Figure 3.3:** Effect of biosorbent dosage to the removal efficiencies of Fe and Mn


The results from Figure 3.3 shows that the maximum biosorption by immobilized *R. Centifolia* waste biomass occurred at 0.05 g/100 ml for both Fe and Mn. This shows that the maximum absorption occurs at minimum dose and hence the amount of metals bound to the absorbent and amount of free metals remained constant. After this dose, the uptake capacity (mg/100ml) of biosorbent was gradually decreased with increase in dose. Amount of biosorbent added to the solution determines the number of binding sites available for absorption. Similar results have been reported by Tariq (2010) and Bhatti (2007).

For effective metal sorption, biosorbent dose is a significant factor to be considered. It determines the sorbent-sorbate equilibrium of the system [25]. Moreover, as the biomass concentration rise, maximum biosorption capacity dropped, indicating poorer biomass utilization (lower efficiency). Results could be explained as a consequence of a partial aggregation, which occurred at high biomass concentration resulted to decrease of active sites.

### 3.4 EFFECT OF PH

Figures 3.4 shows the percentage removal of Fe and Mn at different pH value. From the graph it is shows that the higher the pH the higher the removal of Fe and Mn. Experiments concerning the effect of pH on sorption were carried out within pH range that was not influenced by metal precipitation (as metal hydroxide). The suitable pH ranges for two metal ions were slightly different like in the Figure 3.4 for Mn sorption were performed at the pH range of 1 to 5 and for Fe at pH of 1 to 6.

The biosorption of Mn and Fe on the *R. Centifolia* distillation sludge biomass was observed to be the function of solution pH. The pH is an important parameter in biosorption from aqueous solution because it influences equilibrium by affecting the speciation of the metal ions, solubility of the metal ions, concentration of counter ions on functional groups of the biomass and degree of ionization of the adsorbate during process (Say, 2003) and (Nadeem,2008). Percentage removal efficiency increased steadily with increasing pH. The most adequate sorption pH was 5 for Mn and 6 for Fe.



**Figure 3.4:** Effect of pH value to the removal efficiencies of Fe and Mn

The increase in biosorption with increase in pH can be explained by the fact that at low pH, the biosorbent surface became more positively charged thus reducing attraction between the biomass and metal ions. These bonded active sites thereafter became saturated and was inaccessible to other cations [35]. Moreover, as the pH is increased, the ligands such as carboxyl, sulfhydryl, phosphate others groups would be exposed, increasing the negative charge density on the biomass surface, resulting in greater attraction between metallic ions and ligands [35].

### 3.5 BATCH REACTOR PERFORMANCE

From batch experiment the optimum condition result is analysed. The optimum condition for contact time is 240min while for biosorbent dosage optimum condition is 0.05g/100ml for both Fe and Mn. For pH value, the optimum condition for percentage removal of both Fe and Mn is different which pH 5 is for Mn and pH 6 for Fe. For this study, pH 5 was selected to be used as the optimum condition. Table 3.2 showed the percentage removal of all parameter compare with the NDWQS using the optimum condition of contact time, biosorbent dosage and pH range.

**Table 3.2:** Percentage removal of all parameters from optimum condition

Parameters	Unit	Groundwater Sample			National Drinking Water Quality Standard (NDWQS)
		Before	After	Percentage Removal (%)	
pH	-	6.99	7.12	1.83	6.5-8.5
COD	mg/l	71	52.38	26.23	10
BOD	mg/l	52.99	32.28	39.08	1
TSS	mg/l	16.72	12.35	26.14	25
Nitrate	mg/l	5.1	26.4	-	10
Ammonia Nitrogen	mg/l	4.38	33	-	0.1
Fe	mg/l	2.37	0.009	99.55	0.3
Mn	mg/l	0.722	0.11	76.73	0.1

Table 3.2 shows that the percentage removals of Fe is higher than percentage removal of Mn with the value of 99.62% and 82.78% for Fe and Mn respectively. Both Fe and Mn are complying with NDWQS [36]. The percentage removal for pH is about 1.83% while for TSS is 26.14%. Both pH and TSS results are comply with NDWQS. Other parameter namely, COD, BOD, Nitrate and Ammonia Nitrogen are higher than acceptable level following NDWQS [37]. These results indicate that biosorbent only effective in removing of inorganic in groundwater sample.

### 3.5.1 IRON (FE) REMOVAL

Iron (Fe) being the fourth most abundant element and second most abundant metal in the earth's crust is a common constituent of groundwater [4,13]. According to the value in Figures 3.5, the influent data shows that Fe concentration in average 2.37mg/l. The high presence of iron in groundwater is generally attributed to the dissolution of iron bearing rocks and minerals, chiefly oxides (hematite, magnetite, limonite), sulphides, carbonates and silicates under anaerobic conditions in the presence of reducing agents like organic matter and hydrogen sulphide [39,40]. From Figure 3.5 the Fe concentration before the treatment is high compared to standard and it is out of the compliance range. After the treatment, the concentration of Fe is achieved the compliance range of the standard which is the Fe concentration is less than 1mg/l.




Figure 3.5: Average Iron (Fe) before and after treatment

Figure 3.6 shows that the percentage removal of Fe in this study was very high which is in average of 99.55%. According to Mubashir (2007) has obtained Pb (II) removals of 87.74% and Zn (II) with 73.8%. While Tariq (2010) has reported that Pb (II) removal is increasing to 95.67% by treating immobilized biomass with different chemical reagents (H<sub>2</sub>SO<sub>4</sub>, HCl and H<sub>3</sub>PO<sub>4</sub>). In this study, the results were in good agreement with previous researcher which is in the range of 70% to 88% ion metals removal [31].




Figure 3.6: Graph of Iron (Fe) percentage removal

### 3.5.2 MANGANESE (MN) REMOVAL

Mn is a transition element that rarely exceeds 0.1 milligram per liter (mg/L) in natural water. In most of all the collected water samples there is a slight excessive level of Mn, hence there is an oily taste. According to the value in Figures 3.7, the influent data shows that average value Mn concentration is 0.73mg/l. The high presence of Mn causes adverse health effects in fact, essential to the human diet. However, water containing excessive amounts of Mn can stain clothes, discolor plumbing fixtures, and sometimes add a "rusty" taste and look to the water [42]. The Mn concentration before the treatment is high compare to standard and it is out of the compliance range. After the treatment, the concentration of Mn achieved the compliance with the standard which is the Mn concentration which is less than 0.1mg/l.





Figure 3.7: Average Manganese (Mn) before and after treatment

Figure 3.8 shows that the percentage of Mn removal in this study is in average of 76.73%. The maximum percentage removal of Mn is 89.93% while the minimum percentage removal is

64.14%. According to previous studies, (Abdul, 2009) have obtained Cu (II) removals of 55.79% and Sayed (2010) have reported Cu (II) 71.24% of removal. In this study, the results were in good agreement with those determined by other researcher which is in the range of 50% to 75% of ion metals removal.



**Figure 3.8:** Graph of Manganese (Mn) percentage removal

#### 4.0 CONCLUSIONS

This study concluded that *R. Centifolia* is an effective biosorbent in ferum and mangan removal. The optimum condition of heavy metal removal was found to be at 240min contact time, pH 5 and 0.05g/100ml dosage of *R. Centifolia*. The highest amount of Fe and Mn removal are 99.55% and 76.73% respectively. In this study parameter such as Fe, Mn, COD, BOD, pH and TSS show a reduce trend after the treatment, while other parameter such as Nitrate and Nitrogen Ammonia show unpromising result. These result show that *R. Centifolia* is effective to treat inorganic in compare to organic pollutant. The results of Fe and Mn removal in groundwater show that *R. Centifolia* is a promising biosorbent. Almost all parameter tested using groundwater show that the groundwater is safe to be consumed after treatment process using biosorbent as it follow acceptable level following limit provided by World Health Organization [41].

#### ACKNOWLEDGEMENT

Authors are thankful to Dr. Aeslina Bt Abd Kadir , Dr. Norzila Bt Othman and Pn Sabariah Musa from UTHM for their aid during present studies.

#### REFERENCES

- [1] Das Gupta A (1991), "Study on groundwater quality and monitoring in Asia and the Pacific". In : Groundwater Quality and Monitoring in Asia and the Pacific. Water Resources Series No 70, ESCAP, Bangkok, p 13-99.
- [2] EEA (1999), "Groundwater quality and quantity in Europe". June 1999, European Environmental Agency, Copenhagen, Denmark.
- [3] Sampat, P. (2000), "Groundwater shock". World Watch, January/February, 10 22.
- [4] Fetter C.W. (2001), "Applied Hydrogeology" Fourth Edition, Prentice Hall, Inc.

- [5] McCarty P.L, (1994), "An Overview of Anaerobic Transformation of Chlorinated Solvents". EPA Symposium on Intrinsic Bioremediation of Groundwater. Office of research and Development, U.S. Environmental Protection Agency, Washington, D.C. p. 135-142
- [6] Madhumita Das (2008), "Groundwater contamination due to manganese mining and its impact on health of mineworkers- a case study". Utkal University (India) Shreerup Goswami, Fakir Mohan University (India).
- [7] Marcovecchio J.E, Botte S.E, Freije R.H (2007), "Heavy Metals, Major Metals, Trace Elements. In: Handbook of Water Analysis". L.M. Nollet, (Ed.). 2nd Edn. London: CRC Press, pp.275-311.
- [8] Biswas, A.K. (1997), "Water Resources: Environmental Planning Management and Development". McGrawHill.
- [9] Francesca, P. (2002), "Biosorption Of Binary Metal Systems Onto An Olive Pomace: Equilibrium Modelling". Department of Chemistry - University of Rome.
- [10] Katko T.S, (1997), "Water! Evolution of Water and Sanitation in Finland from the mid-1800s to 2000". Finnish Water and Waste Water Association; Hameen Kirjapaino Ltd., Tampere.
- [11] U.S. Environmental Protection Agency, (1992), "Lead Poisoning and Your Children, (800-B-92-0002)". Washington, D.C.: Office of Pollution Prevention and Toxics.
- [12] Adeyemi O, Oloyede O.B, Oladiji, A.T (2007), "Physicochemical and Microbial Characteristics of Leachate-contaminated Groundwater". Asian. J. Biochem. 2(5): 343-348.
- [13] Agency for toxic Substance and Disease Registry ASCE. (1990), "Toxicological profile for lead—draft. Atlanta: Evapotranspiration and irrigation water requirements". Manuals and reports on engineering practice. New York, NY, USA.
- [14] Cynthia R. Evanko, David A. Dzombak. (1997), "Remediation of Metals Contaminated Soils and Groundwater prepared". P.E. Carnegie Mellon University Department of Civil and Environmental Engineering Pittsburgh.
- [15] Adesola Babarinde N.A, (2007), "Isotherm and thermodynamic studies of the biosorption of copper (II) ions by *Erythrodontium barteri*". International Journal of Physical Sciences Vol. 2 (11), pp. 300-304.
- [16] Adeyemi O, Oloyede O.B, Oladiji, A.T (2007), "Physicochemical and Microbial Characteristics of Leachate-contaminated Groundwater". Asian. J. Biochem. 2(5): 343-348.
- [17] Delleur J.W. (1999), "The handbook of Groundwater Engineering". Indiana U.S.A. RC Press & Springer. Verlag Publisher.
- [18] Mohammad Hassan Khani (2005), "Biosorption Of Uranium From Aqueous Solutions By Nonliving Biomass Of Marinealgae *Cystoseira Indica*". Atomic Energy Organization of Iran Jaber Ibn Hayan Research Laboratories Tehran, Iran.
- [19] Siti Aishah A. W. (2009), "Biosorption Of Lead (II) From Aqueous Solution by Dried Water Hyacinth (*Eichhornia Crassipes*)". University Malaysia Pahang (Malaysia).
- [20] Ozdemir G, Ozturk T, Ceyhan N, Isler R, Cosar T. (2003), "Heavy metal biosorption by biomass of *Ochrobertrum anthropi*". Proceeding exo-polysaccharide in activated sludge, Bioresour. Technol 90, pp: 71–74.
- [21] Quek S.Y, Wase D.A.J, Forster C.F, (1998), "The use of sawwaste for the sorption of lead and copper". Water SA 24, pp: 251–256.
- [22] Kratochvil D, Pimentel P.F, Volesky B, (2000), "Removal of trivalent chromium by seaweed biosorbent", Department of Chemical Engineering, McGill University, Montreal, Quebec, Canada,.

- [23] Bhatti H.N, B. Mumtaz, M.A. Hanif, R. Nadeem, (2007), "Removal of Zn(II) ions from aqueous solution using *Moringa oleifera* lam. (Horseradish tree) biomass", *Process Biochem*, 42, pp: 547–553.
- [24] Narioka Hajime, (2003), "Changes in Level of Groundwater Table and its Conservation: The Case of the Ohba Magistrate Office, Setagaya-ku, Tokyo", *J.Japan Soc. Hydrol. & Water Resour*, 16 (6), pp: 631-639.
- [25] Hanif M.A, Nadeem R, Zafar M.N, Akhtar K, Bhatti H.N. (2007), "Kinetic studies for Ni (II) biosorption from industrial wastewater by *cassia fistula* (Golden shower)". *Biomass J. Hazard Mater* 145, pp: 501-505.
- [26] Javed MA, Bhatti HN, Hanif MA, Nadeem R (2007), "Kinetic and equilibrium modeling of Pb(II) and Co(II) sorption onto rose waste biomass". *Sep Sci. Technol.* In press.
- [27] Silverstein R.M., F.X. Webster, (1998), "Spectrometric Identification of Organic Compounds". 6<sup>th</sup> ed., John Wiley & Sons,.
- [28] Nasir MH, Nadeem R, Akhtar K, Hanif MA, Khaild AM (2007), "Efficacy of modified distillation sludge of rose (*Rosa centifolia*) petals for lead (II) and Zn (II) removal from aqueous solutions". *J Hazard Mater*; In press.
- [29] Padmavathy V, Vasudevan P, Dhingra S.C, (2003), "Thermal and spectroscopic studies on sorption of nickel (II) ion on protonated baker's yeast". *Chemosphere*, 52, PP: 1807–1817.
- [30] Haq Nawaz Bhattia, Rabia Khalida, Muhammad Asif Hanifa (2009), "Dynamic biosorption of Zn(II) and Cu(II) using pretreated *Rosa gruss an teplitz* (red rose) distillation sludge". *Chemical Engineering Journal* 148, pp: 434–443.
- [31] Tariq Mahmood Ansari, (2010), "Immobilization of Rose Waste Biomass for Uptake of Pb(II) from Aqueous Solutions". Department of Environmental Sciences, GC University, Pakistan
- [32] Bhatti H.N, B. Mumtaz, M.A. Hanif, R. Nadeem, (2007), "Removal of Zn(II) ions from aqueous solution using *Moringa oleifera* lam. (Horseradish tree) biomass". *Process Biochem* 42, pp: 547–553.
- [33] Say R., N. Yilmaz, A. Denizli (2003), "Biosorption of cadmium, lead, mercury and arsenic ions by the fungus *Penicillium purpurogenum*, Sep". *Sci. Technol.* 38, pp: 2039–2053.
- [34] Nadeem R., Hanif M. A, Shaheen F, Perveen S, Zafar M. N, Iqbal T, (2008), "Physical and chemical modification of distillery sludge for Pb(II) biosorption". *J. Hazard.Mater*, 150, pp: 335–342.
- [35] Yu J, M. Tong, X. Sun, B. Li, (2006), "Cystine-modified biomass for Cd(II) and Pb(II) biosorption", *J. Hazard. Mater.* 132, pp: 126–139.
- [36] Nash, H. and McGall, G.J.H. (1994), "Groundwater Quality". 17th Special Report. Chapman & Hall.
- [37] Hussein H, Ibrahim S.F, Kandeel K, Moawad H, (2004), "Biosorption of heavy metal from wastewater using *pseudomonas sp*". *Eur. J. Biotechnol*, 7, pp: 1–7.
- [38] Hem, J.D. (1989), "Study and Interpretation of the Chemical Characteristics of Natural Water". 3<sup>rd</sup> ed, USGS, Water Supply Paper 2254.
- [39] Nelder J.A, R.Mead, (1965), "A simplex method for function minimization". *Comput. J. Vol.* 7, pp: 308–315.
- [40] Nomanbhay S.F. , K. E. J. (2005), "Palanisamy", *Biotechnol.* 8, 44,
- [41] WHO (1996), "Guideline for the Promotion of Human Rights of persons with mental disorders". Geneva, World Health Organization.

- [42] Adepoju-Bello A.A, Ojomolade O.O, Ayoola G.A, Coker AAB (2009), “Quantitative analysis of some toxic metals in domestic water obtained from Lagos metropolis”. *The Nig. J. Pharm.*, 42 (1): 57-60.
- [43] Abdur Rauf Iftikhar (2009), “Kinetic and thermodynamic aspects of Cu(II) and Cr(III) removal from aqueous solutions using rose waste biomass”. Industrial Biotechnology Laboratory, Department of Chemistry, University of Agriculture, Faisalabad, Pakistan.
- [44] G.O El-Sayed (2010), “Biosorption Of Ni (II) And Cd (II) Ions From Aqueous Solutions Onto Rice Straw”. Chemistry Department, Faculty of Science, Benha University, Benha, Egypt.
- [45] Mubashir Hussain Nasir (2010), “Efficacy of modified distillation sludge of rose (*Rosa centifolia*) petals for lead(II) and zinc(II) removal from aqueous solutions”. Department of Chemistry, University of Agriculture, Faisalabad (38040), Pakistan.
- [46] Keskin O. (2003), “Heavy metal adsorption properties of a submerged aquatic plant (*Ceratophyllum demersum*)”, Department of Environmental Engineering, Faculty of Engineering, Cukurova University, Turkey